



MATERIAL SAFETY DATA SHEET

HEAT RESISTANT CLEAR

Page: 1

Revised Date:

1/1/2006

PRODUCT NAME: HEAT RESISTANT CLEAR
PRODUCT CODE: 35LG003

HMIS CODES: H F R P
2*3 0 H

SECTION I - MANUFACTURER IDENTIFICATION

MANUFACTURER'S NAME: DREW PAINTS, INC.

ADDRESS : P.O. BOX 29139
: PORTLAND, OREGON 97296-9139

EMERGENCY PHONE : (800) 424-9300

DATE PRINTED : 10/25/2007

INFORMATION PHONE : (503) 227-6497

NAME OF PREPARER : KIEFFER TARBELL

SECTION II - HAZARDOUS INGREDIENTS/SARA III INFORMATION

REPORTABLE COMPONENTS	CAS NUMBER	VAPOR PRESSURE mm Hg @ TEMP		WEIGHT PERCENT
*Ü XYLENE OSHA PEL: 100 PPM, ACGIH TLV: 100 PPM	1330-20-7	6	68	23.35
*Ü META-XYLENE OSHA PEL: 100 PPM, ACGIH TLV: 100 PPM	108-38-3			14.65
*Ü ETHYL BENZENE OSHA PEL: 100 PPM, ACGIH TLV: 100 PPM	100-41-4	7.1	68	11.95
*Ü ORTHO-XYLENE OSHA PEL: 100 PPM, ACGIH TLV: 100 PPM	95-47-6			6.47
*Ü PARA-XYLENE OSHA PEL: 100 PPM, ACGIH TLV: 100 PPM	106-42-3			6.47

* Indicates toxic chemical(s) subject to the reporting requirements of section 313 of Title III and of 40 CFR 372. Ü Indicates Hazardous Air Pollutants according to the 1990 Clear Air Act Amendments regulated under Section 112, as published by Oregon Department of Environmental Quality, January 1994.

SECTION III - PHYSICAL/CHEMICAL CHARACTERISTICS

BOILING RANGE: 275 deg F - 281°F

SPECIFIC GRAVITY (H2O=1): .95

VAPOR DENSITY: HEAVIER THAN AIR

EVAPORATION RATE: SLOWER THAN ETHER

COATING V.O.C.: 5.06 lb/gl

MATERIAL V.O.C.: 5.06 lb/gl

SOLUBILITY IN WATER: ESSENTIALLY NIL

APPEARANCE AND ODOR: OPAQUE COLOR WITH AN ODOR OF PAINT THINNER

SECTION IV - FIRE AND EXPLOSION HAZARD DATA

FLASH POINT: 72 deg F

METHOD USED: TCC

FLAMMABLE LIMITS IN AIR BY VOLUME- LOWER: 1

UPPER: 7

EXTINGUISHING MEDIA: FOAM, CO2, DRY CHEMICAL

SPECIAL FIREFIGHTING PROCEDURES



MATERIAL SAFETY DATA SHEET

HEAT RESISTANT CLEAR

Page: 2

Revised Date: 1/1/2006

USE SELF-CONTAINED BREATHING APPARATUS TO AVOID INHALATION OF CONCENTRATED VAPORS. FULL STREAM WATER MAY BE UNSUITABLE AS EXTINGUISHING METHOD. WATER SPRAY MAY BE USED TO COOL SEALED CONTAINERS.

UNUSUAL FIRE AND EXPLOSION HAZARDS

KEEP CONTAINERS TIGHTLY CLOSED. ISOLATE FROM HEAT, SPARKS, ELECTRICAL EQUIPMENT AND OPEN FLAMES. CLOSED CONTAINERS MAY EXPLODE WHEN EXPOSED TO EXTREME HEAT. WATER FOG MAY BE USED TO COOL UNRUPTURED CONTAINERS. HANDLE AS FLAMMABLE LIQUID.

SECTION V - REACTIVITY DATA

STABILITY: STABLE

CONDITIONS TO AVOID

EXCESS HEAT, SPARKS, OPEN FLAME, POOR VENTILATION, CORROSIVE ATMOSPHERES, AND EXCESSIVE AGING.

INCOMPATIBILITY (MATERIALS TO AVOID)

OXYGEN AND STRONG OXIDANTS. WILL DISSOLVE OR SOFTEN SOME PLASTICS AND RUBBER.

HAZARDOUS DECOMPOSITION OR BYPRODUCTS

THERMAL DECOMPOSITION CAN LEAD TO CARBON MONOXIDE AND CARBON DIOXIDE.

HAZARDOUS POLYMERIZATION: WILL OCCUR

SECTION VI - HEALTH HAZARD DATA

INHALATION HEALTH RISKS AND SYMPTOMS OF EXPOSURE

EXCESSIVE INHALATION OF VAPORS CAN CAUSE NASAL AND RESPIRATORY IRRITATION, DIZZINESS, WEAKNESS, FATIGUE, NAUSEA, AND HEADACHE. HIGH CONCENTRATIONS MAY RESULT IN NARCOSIS. (CENTRAL NERVOUS SYSTEM DEPRESSION)

SKIN AND EYE CONTACT HEALTH RISKS AND SYMPTOMS OF EXPOSURE

EYE CONTACT: SEVERE IRRITATION, REDNESS, TEARING AND BLURRED VISION. LIQUID AND MIST MAY DAMAGE EYES. SKIN CONTACT: PROLONGED OR REPEATED EXPOSURE CAN CAUSE MODERATE IRRITATION, DEFATTING, DERMATITIS.

SKIN ABSORPTION HEALTH RISKS AND SYMPTOMS OF EXPOSURE

BREIF CONTACT MAY DRY THE SKIN. PROLONGED OR REPEATED CONTACT MAY IRRITATE THE SKIN CAUSING DERMATITIS.

INGESTION HEALTH RISKS AND SYMPTOMS OF EXPOSURE

CAN CAUSE GASTROINTESTINAL IRRITATION, NAUSEA, VOMITING AND DIARRHEA. ASPIRATION OF MATERIAL INTO LUNGS CAN CAUSE CHEMICAL PNEUMONITIS WHICH CAN BE FATAL. DO NOT INDUCE VOMITING, SEEK MEDICAL ATTENTION.

HEALTH HAZARDS (ACUTE AND CHRONIC)

IMMEDIATE EFFECTS (ACUTE): EYE IRRITATION. HARMFUL IF INHALED. MAY AFFECT THE BRAIN, NERVOUS SYSTEM OR RESPIRATORY SYSTEM CAUSING DIZZINESS, HEADACHE, NAUSEA OR RESPIRATORY IRRITATION. OVER EXPOSURE TO INGREDIENTS IN THIS PRODUCT MAY CAUSE NOSE, THROAT, EYE, AND SKIN IRRITATION. CHRONIC EXPOSURE MAY CAUSE DAMAGE TO KIDNEYS, CENTRAL NERVOUS SYSTEM, RESPIRATORY SYSTEM, LUNGS, EYES, SKIN, LIVER, SPLEEN, AND GASTROINTESTINAL TRACT. INTENTIONAL MISUSE MAY BE HARMFUL OR FATAL.

CARCINOGENICITY: NTP CARCINOGEN: No IARC MONOGRAPHS: No OSHA REGULATED:
No



MATERIAL SAFETY DATA SHEET

HEAT RESISTANT CLEAR

Page: 3

Revised Date: 1/1/2006

CALIFORNIA PROP. 65 WARNING: THIS PRODUCT CONTAINS A CHEMICAL(S) KNOWN TO THE STATE OF CALIFORNIA TO CAUSE CANCER, BIRTH DEFECTS, OR OTHER REPRODUCTIVE HARM.

MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE

ANESTHESIA, ALLERGY, RESPIRATORY IRRITATION, DERMATITIS, NAUSEA, & SENSITIZATION

EMERGENCY AND FIRST AID PROCEDURES

INHALATION- REMOVE TO FRESH AIR. RESTORE BREATHING. CONTACT PHYSICIAN. EYE CONTACT- FLUSH WITH LARGE AMOUNTS OF WATER OR EYE WASH. CONTACT PHYSICIAN. SKIN CONTACT- REMOVE CONTAMINATED CLOTHING. WASH SKIN THOROUGHLY W/ SOAP & WATER. CONTACT PHYSICIAN IF NECESSARY. INGESTION- DO NOT INDUCE VOMITING, CAN CAUSE CHEMICAL PNEUMONITIS & PULMONARY EDEMA. CONTACT PHYSICIAN IMMEDIATELY.

SECTION VII - PRECAUTIONS FOR SAFE HANDLING AND USE

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED

REMOVE SOURCES OF IGNITION, USE RESPIRATORY PROTECTION & PROTECTIVE CLOTHING. DIKE SPILL & USE ABSORBANT MATERIAL TO RECOVER SPILLED LIQUID. VENTILATE AREA.

WASTE DISPOSAL METHOD

DISPOSE OF WASTE IN ACCORDANCE WITH ALL LOCAL, STATE, AND FEDERAL REGULATIONS. BEFORE ATTEMPTING CLEANUP, REFER TO HEALTH & REACTIVITY HAZARD INFORMATION IN SECTIONS V & VI. DO NOT INCINERATE CLOSED CONTAINERS.

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING

KEEP CONTAINERS CLOSED WHEN NOT IN USE. KEEP AWAY FROM EXCESSIVE HEAT AND OPEN FLAMES. USE SPARKPROOF TOOLS AND EQUIPMENT. USE IN WELL VENTILATED AREAS. FREE FALLING STREAMS MAY CAUSE STATIC BUILDUP, GROUND CONTAINERS WHEN TRANSFERRING.

OTHER PRECAUTIONS

"EMPTY" CONTAINERS MAY BE HAZARDOUS FROM RESIDUES OF PRODUCT AND VAPOR AND ALL CAUTIONS ON THIS SHEET APPLIES TO THEM. SMOKING IN AREAS WHERE THIS MATERIAL MAY BE USED SHALL BE PROHIBITED. DO NOT TAKE INTERNALLY. AVOID SKIN CONTACT.

SECTION VIII - CONTROL MEASURES

RESPIRATORY PROTECTION

WHEN SPRAYING THIS MATERIAL USE A NIOSH APPROVED CARTRIDGE RESPIRATOR OR GAS MASK SUITABLE TO KEEP AIRBORNE MISTS AND VAPOR CONCENTRATIONS BELOW THE TIME-WEIGHTED THRESHOLD LIMIT VALUES. WHEN USING IN POORLY VENTILATED AND CONFINED SPACES, USE A FRESH-AIR SUPPLYING RESPIRATOR OR A SELF-CONTAINED BREATHING APPARATUS.

VENTILATION

GENERAL MECHANICAL VENTILATION OR LOCAL EXHAUST SHOULD BE SUITABLE TO KEEP VAPOR CONCENTRATIONS BELOW TLV. VENTILATION EQUIPMENT MUST BE EXPLOSION PROOF.

PROTECTIVE GLOVES

IMPERMEABLE CHEMICAL HANDLING GLOVES FOR SKIN PROTECTION.



MATERIAL SAFETY DATA SHEET

HEAT RESISTANT CLEAR

Page: 4

Revised Date:

1/1/2006

EYE PROTECTION

USE CHEMICAL SAFETY GLASSES, GOGGLES, & FACESHIELDS FOR EYE & FACE PROTECTION.

OTHER PROTECTIVE CLOTHING OR EQUIPMENT

USE IMPERMEABLE APRONS & PROTECTIVE CLOTHING WHENEVER POSSIBLE TO PREVENT SKIN CONTACT. THE USE OF HEADCAPS AND BOOTS, WHEN POSSIBLE IS STRONGLY RECOMMENDED.

WORK/HYGIENIC PRACTICES

WASH THOROUGHLY AFTER HANDLING THIS PRODUCT. IF CLOTHING IS CONTAMINATED, DISCARD OR LAUNDRER.

SECTION IX - DISCLAIMER

THE INFORMATION CONTAINED HERIN IS BASED ON DATA CONSIDERED TO BE ACCURATE. DREW PAINTS, INC. MAKES NO WARRANTIES EXPRESSED OR IMPLIED AND ASSUMES NO RESPONSIBILITY FOR THE ACCURACY OR COMPLETENESS OF THE DATA. DREW FURTHER ASSUMES NO RESPONSIBILITY FOR PERSONAL INJURY OR PROPERTY DAMAGE TO VENDEES, USERS, OR THIRD PARTIES CAUSED BY THIS MATERIAL.